Fukushima Daiichi –

nuclear disaster

Avtor: Gabrijela Ikovic

Mentor: prof. dr. Iztok Tiselj


Jedrska tehnika in energetika 2012/13

The eartquake:

- March 11,2011
- earthquake magnitude 9.0
- tsunami waves up to 40.5 metres


• nuclear power plants automatically shut downshia (1)

destroyed diesel backup power systems





Tsunami



Cooling systems

- every reactor unit has emergency cooling system
- after the earthquake : HPCI (high pressure cooling injections)
- passive cooling systems designed to work without electricity (steam from reactor)
- Unit #1 : 0h ICC(isolation core cooling) failed
- Unit#2 : 70h RCIC(reactor core isolation cooling)
- Unit#3: 40h RCIC/HPCI

Core melting

Energy balance:

1) Decay heat 10-20 MWh/h

2) Over 1500 K – fast reaction Zirconium - water (50 ton Zr):

 $Zr + 2H_2O -> ZrO_2 + 2H_2 + \sim 20 \text{ MWh/}10 \text{ ton } Zr$


3) Combustion H₂

~20 MWh/10 ton Zr

-1) Evaporation H_2O ~5 MWh/10 ton (3 h ~ 100 ton) water ~100-200 ton, unknown leaking

-2) heating and melting of the fuel and other parts of reactor


~20 MWh/100 ton UO₂




Core melting

- about 1500°C
- fuel rod cladding melts, releasing radioactive isotopes (Cs,I, ...) into damaged containment building
- radiation escapes into enviroment
- some of the fuel remains inside of the vessel, some had been leaking through the holes at the bottom

Melted core






In reactor unit#1 70% of the fuel had been damaged(left) in units#2 & #3 30-35% (right).

Hydrogen explosion


- Unit#1, Unit#3 and Unit#4
- for explosion to occur the reactor must be damaged
- exposed fuel rods (Zr) reacts with steam, producing hydrogen
- high concentration of hydrogen a spark triggers the explosion

Hydrogen explosion in the operation floor



Cooling

- Seawater injected with fire trucks
- 10 houres to fill the reactor and 10 days to cool it down
- adding boric accid as a neutron absorber



Spent fuel pools

First few weeks:

Cooling with external water cannons (#1 & #4) – 2 weeks sea water, later fresh water

Structural integrrity of pool #4 was questionable – explosion(H2 from unit#3)


Pools #2 and #3 – standard cooling system (8.5.2011)

Pools of unit #5 and #6 and main pool: cooling systems were working normaly all the time


Temperatures: 30-40 °C



Source: Asahi.com










After six months...


- reactors 1,2,3 injecting water into reactor vessel (3.5, 3.5, 8 m³/h) T_{vessel} : ~90-120 °C; p~1 bar (TEPCO 2.9.2011)
- damaged infrastrukture
- leaking of radioactive water
- decontamination of water

First 2-3 months water had not been "recycled" -> ~110000 ton highly radioactive water.



How a nuclear plant meltdown could unfold

An explosion at an earthquake-hit nuclear plant in Japan has sparked fears of a radiation leak and nuclear meltdown. A meltdown occurs when failure of the cooling system leads to fuel rods overheating and melting



Viri:

- http://www.icjt.org/aktualno/Fukushima.htm
- http://www.ursjv.gov.si/si/info/fukushima/
- http://sl.wikipedia.org/wiki/Jedrska_katastrofa_v_elektrar
 ni_Fuku%C5%A1ima-Dai%C4%8Di
- http://en.wikipedia.org/wiki/Fukushima_Daiichi_nuclear_ disaster
- http://bubasvabe.blog.siol.net/2011/03/15/fukushima/
- http://en.wikipedia.org/wiki/Nuclear_reactor_safety_systemms#Emergency_core_cooling_system_.28ECCS.29