

Meritev intenzivnosti 12.5.2006

Tretja skupina

Vir: Sound Power Source B&K 4205; nastavljen na wide band 100 Hz - 10 kHz; power na 80,0 dB. Mreža: kocka 0,5 x 0,5 m vsaka stranica ima 5 x 5 = 25 kvadratov s stranico 10 cm. Ker je vir simetričen izmerimo samo eno stransko stranico (namesto štirih) (file = 3-str1.mip) in eno na vrhu kocke (file = 3-str5.mip)

Stranica 1 (ostale 3 stranice enake)

Nivo intenzivnosti Litot (dBA)

5	77.4	79.0	79.7	78.8	77.6
4	77.6	79.8	81.0	80.2	78.4
3	76.5	79.0	80.2	79.2	76.9
2	73.7	74.4	76.0	75.4	73.3
1	74.7	73.9	74.4	73.8	74.1
	1	2	3	4	5

Stranica 5 (zgornja stranica)

Nivo intenzivnosti Litot (dBA)

5	78.3	80.0	80.7	80.1	78.4
4	79.8	82.4	83.5	82.4	80.0
3	80.6	83.8	85.2	83.9	81.1
2	80.3	82.8	84.3	83.4	80.8
1	78.8	80.8	81.5	80.9	79.2
	1	2	3	4	5